



CCS-300D

Direct Thermal Barcode Printer

- Space-saving design, 32 bit process
- Ultra fast print speed : 152 mm/s
- Bi-colored status LEDs for quick printer status
- Rich emulation language compatibility: TSPL, ZPL, EPL, DPL.





CCS-300D

Direct Thermal Printer



Printing Features	
Resolution	203 DPI
Print method	Direct Thermal
Print speed	152mm(6")/s
Max.print width	108 mm (4.25")
Max.print length	1778 mm (70")
Media	
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	25.4~115mm
Media thickness	0.06 mm ~0.254 mm
Label length	10~1778 mm (0.39"~70")
Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM/ Flash memory can be expanded Max.4Gb
Interface	Standard version: USB Optional:WIFI/Bluetooth/TF card
Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11
2D barcode	PDF-417,Maxicode,DataMatrix, QR code
Rotation	0°、90°、180°、270°
Emulation	TSPL、EPL、ZPL、DPL
Physical Features	
Dimension	127.8 mm (W) x 117.8 mm (H) x 182.9 mm (D)
Weight	1.1 kg
Reliability	
Warranty	One year for the printer
Print head	30 km
Software	
Driver	Windows / Linux / Mac
SDK	Windows / iOS / Android
Power supply	
Input	AC 100-240V
Output	DC 24V / 2.5A
Options	
Factory Options	① Bluetooth module ② WiFi module ③ Real Time Clock ④ TF card
Dealer Options	① External paper roll holder and 1 "paper roll ② Extension board for external paper roll holder ③ Shipment waybill box
Environmental Conditions	
Operation	5 ~ 40°C(41~104°F) , Humidity: 25 ~ 85% non-condensing
Storage environment	-40 ~ 60°C(-40~140°F) , Humidity:10 ~ 90% non-condensing

Sole Distributor for Bangladesh

Cortex Control Solution

A Sister Concern of

GENERAL AUTOMATION LTD.
Automation & Communication Since 1991

Tel : +88-02-41022433-34, +88-02-41022461, Hot Line # 01730066010
E-mail: info@cortexcontrolsolution.com , Web : www.cortexcontrolsolution.com

