



## CCS-T2A

### Thermal Receipt Printer

- Support QR code
- Easy paper loading
- High operational reliability
- High print speed for both graphics and text
- Supports a variety of international languages



Store



Hospital



Café




Logistics





# CCS-T2A

## Thermal Receipt Printer



<b>Printing</b>		<b>CCS-T2A</b>
Printing method	Direct thermal	
Paper width	57.5±0.5mm	
Print width	48 mm	
Column capacity	384 dots/line(adjustable by command)	
Printing speed	90mm/s	
Interface	USB/USB+Serial / USB+Bluetooth/ USB+Bluetooth+Serial / USB+Bluetooth+Serial+WIFI	
Line spacing	3.75mm (Adjustable by commands)	
<b>Fonts Symbolologies</b>		
Character size	Font A: 12x24;Font B: 9x17;CHN: 24*24	
Characters /Line	Font A: 32 chars;Font B: 42 chars;CHN: 16 Character Sets	
1D Barcode	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128	
2D Barcode	QR code	
Input buffer	32 Kbytes	
NV Flash	64 Kbytes	
<b>Power</b>		
Power adaptor	AC 110V/220V, 50~60Hz; DC 12V/2.6A	
Power source	DC 12V/2.6A	
Cash drawer output	DC 12V/1A	
<b>Physical characteristics</b>		
Weight	0.498 KG	
Dimensions	121.8*110*114.6mm(D*W*H)	
<b>Environmental Requirements</b>		
Work environment	Temperature (0~45°C); humidity(10~80%)	
Storage environment	Temperature(-10~60°C); humidity(10~90%)	
<b>Reliability</b>		
Printer head life	50KM	
<b>Software</b>		
Emulation	ESC/POS	
Driver	Windows/JPOS/Linux/Android/Mac	
Utility	Windows & Linux test Utility	
SDK	IOS/ Android/ Windows	

Sole Distributor for Bangladesh

### Cortex Control Solution

A Sister Concern of

**GENERAL AUTOMATION LTD.**  
Automation & Communication Since 1991

Tel: +88-02-41022433-34, +88-02-41022461, Hot Line # 01730066010  
E-mail: info@cortexcontrolsolution.com, Web: www.cortexcontrolsolution.com

